		(When Filled In) REPLY RE	QUESTED DATE	mangan mggana ng bidan bida d 1884 - Bilak 1994 - 180 A	
OFY/A A	SPEED LETTER	YES	NO LETTER		
25X1A		FROM:		<u>-</u>	
TTN:					ye-
Control of the second of the s		12. 7			e e e e e e e e e e e e e e e e e e e
Gom action	and appropriately	. Els han Ti	4. hutezate e	toneuweace floor	m E
	00				To the Section Control of the Contro
Theles		1			
<u> LL</u>	EGIB	* · · · · · · · · · · · · · · · · · · ·		na . n.e. a	<u> </u>
					1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
				ः द ; ः च ।	er in de la companya (no de la comp En la companya (no de la companya
				<u>: :</u>	
				A STATE OF THE STA	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
interest of the second of the	- 第21 日 第7章 (1838年 - 1838年 - 18384年 - 1838年 - 1838年 - 1838年 - 18384年 - 18384年 - 18384年 - 18384 - 18384 - 18384 - 18384 - 18384 - 18384 - 18384 - 18384 - 183		25X1A	100 100	The second second
r i ni e u partient riter			25X IA		
State of the state			·	Communication (Communication Communication C	AND THE RESIDENCE OF THE PROPERTY OF THE PROPE
Figure and company of the company of	and and the first section of the control of the con		to the state of th	SIGNATURE	
	REPLY		DATE	स्थान के काल किया किया है के किया के किया किया किया किया किया किया किया किया	der Libertin zur der Weistern Britister
S SERVICE CONTINUES OF SERVICES OF SERVICE					
and come the plants and come		and the state of t	gara saga aya giliyili		477
- AD	edingeras	stair	-units	renduces	
			· · · · · · · · · · · · · · · · · · ·		The second secon
are 6	HAMM				
	an farina de la camera de la camera de la comercia de la camera de la camera de la comercia de la comercia de La camera de la camera de la comercia de la camera de la c La camera de la camera de la comercia de la camera de la c			יים מיים ליים מיים או מיים מיים מיים מיים מיים מיים מיים מיי	
	Declass Review by	/ NIMA/DOD			TOTAL CONTROL OF THE PROPERTY
			\$\frac{1}{2} \cdot \frac{1}{2}		
The state of the s		HA ME DIE CO. COMPANIENTE DE PARTIE DE L'ANDIE DE L'AND	BLAT S DIG HAMPSHOOTH JELLING VINCHING HOME SAMEL		
		2	5X1A		
	. Parting of the Color of the C			n de la la elementa de la calenda de la cale	18
					2 STORES FRANCE

Approved For Release 2001/03/04/FIDENTIA 8B04747A000400040001-3

18 September 1967 Ref: SJO 860-1445

25X1A



Contracting Officer

25X1A

Subject:

Dear Sir:

In 1965, we submitted a Specification and Amendment I for a Chip Format Printer which are now the governing documents for Phase II of the subject contract. Since that time, many improvements and minor changes to the equipment have been made which were required for better equipment operation and which were not apparent to us in 1965 when the original Specification was written and submitted. Therefore, we are transmitting four (4) copies of Amendment II, dated 6 September 1967, for your review and approval in order to update the original Specification and Amendment I.

Since the equipment is now undergoing preliminary in-house final testing, an early approval of this document would be appreciated.

Very truly yours,

25X1A

Contracts

SJO/cc encls. (4)

25X1A

cc w/encl. to:

*This Document contains information affecting the National Defense of the United States within the meaning of the Espionage Lana, Title 18, U.S.C., Sections 793 and 794, the transmission or revelation of which in any manney to an unsufficient by law.

EXCLUDED FROM AUTOMATIC REGRADING: DGD DIR 5200.10

3 PANTINENT A BO4747A0004QQQ4QQ04QQQ

Approved For Release 2001/03/06 : CIA-RDP78B04747A000400040001-3

AMENDMENT II

TO
CHIP FORMAT PRINTER SPECIFICATION
DATED 7 JULY 1965 and
AMENDMENT I
DATED 15 OCTOBER 1965

STATINTL

Prepared by:

Approved For Release 2001/03/06: CIA-RDP78B04747A000400040001-3

The following is a list of changes to the 7 July 1965 Specification and 15 October 1965 Specification Amendment I for the Chip Format Printer.

Paragraph 1.1(e) - Specification

This paragraph calls for an air mounted vibration isolator system. Because of some serious shortcoming of these mounts, cable isolators were installed in their place.

Delete:

e (1) An Air-Mounted Vibration System

Add:

e (1) Cable Isolators

Paragraph 2.2.1 - Specification and 4.3 - Amendment

Delete 0.003 inches to 0.012 inches. Add 0.003 to 0.0075 in their place.

Paragraph 2.3.1 - Specification

Delete ninety (90) and add eighty (80).

Paragraphs 2. 3. 1. 1 and 2. 3. 1. 2 and 2. 3. 1. 3 and 2. 4. 1 - Specification

An additional character has been added to the tape format raising the total number of control characters to 25. This character will be on Information Separator (code S₇) between the last word of Number of Prints and Start of Message. Also, adjacent messages on the input tape should be separated by a series of spaces for leader. Therefore, delete all references to 24 and add 25 in their place.

Paragraph 2.4.2(a) - Specification

Paragraph 2. 4. 2(b) - Specification

<u>Delete</u> the first sentence, "The alpha-numerical......font." <u>Add</u> the first sentence, "The alpha-numerical display and the digital display will be generated by utilization of a constantly rotating font."

Approved For Release 2001/03/06 : CIA-RDP78B04747A000400040001-3









Approved For Release 2001/03/06: CIA-RDP78B04747A000400040001-3

Paragraph 2.4.3 - Specification

8×

Delete the last two sentences starting with, "The symbols.....input tape."

Paragraph 2.6.1 - Specification

STATINTL

STATINTL

A

This paragraph calls out a one run capability of 36. Rework of the processing magazine will reduce this value to 34 minimum. Therefore, delete 36 wherever it appears and add 34 minimum.

Paragraph 2.7.3 - Specification

8P

Add to first sentence after the last word travel "when tested with .0054 ± .0003 inch-thick film."

Paragraph 2.7.4 - Specification and 4.2.1 - Amendment

9K

Delete:

0.1mm.

Add:

0.2mm.

Paragraph 2.7.5 - Specification and 4.2.1 - Amendment

Delete:

1/10 of 1 degree.

Add:

0.2 degrees.

Paragraph 2.7.8 - Specification

gk

Delete:

.10 of a foot.

Add:

0.2 ft.

Paragraph 2.7.10 - Specification

X

Delete the words "six digit" wherever they appear and add "five digit" in their place.

Paragraph 2.8.1(b) - Specification

gr

Delete:

.200 of an inch.

Add.

0.250 of an inch in diameter.

Approved For Release 2001/03/06: CIA-RDP78B04747A000400040001-3

Paragraph 2.8.1(c) - Specification

Delete:

one-half stop

Add: one stop Delete:

 $\pm 1 1/2 \text{ stops}$

Add:

± 3 stops

Paragraph 2.10.4 - Specification

Delete:

Add:

105 108

Paragraph 2.11.3 - Specification



Delete:

"cards"

Add:

"diagrams"

Paragraph 6.1.1 - Specification



Delete "along with" and add after drawings "consisting of only major assemblies and".

Paragraph 1.3 - Amendment



Delete "security classification and etcetera."

Paragraph 4.2.1 - Amendment



Add after ± .3mm "when tested with .0054 ± .0003 inch-thick film."

Paragraph 4.3.1.3 - Amendment

Delete: 1/2 step

Add:

l step



Under Note, delete 1/4 and add 2/3.

General

In the event raw input chips without anti mhalation backing are used in the unit with the liquid gate operating, a variation in density may be experienced around the border of the chip to a depth of approximately 1/4 inch.